

	VF 160	VF 206
<b>Characteristics</b>		
Usable length	6 to 18 m	6 to 18 m
Minimum angle	35 x 35 x 3,5 mm	50 x 50 x 4 mm
Maximum angle	160 x 160 x 17 mm	200 x 200 x 24 mm
Maximum flat bar	160 x 17 mm	200 x 25 mm
Carriage maxi speed	60 m/min	60 m/min
<b>Punching</b>		
Number of punching units	2 / 4 / 6	2 (3 tools each)
Punching power	650 kN	1100 kN
Maximum diameter in maximum thickness	Ø 30 in 17 mm	Ø 32 in 25 mm
<b>Marking</b>		
Possible marking power	80 tons	80 tons
Number of barrel stations	8 of 10 characters	9 of 10 characters
<b>Shearing</b>		
Shearing power	2200 kN	4000 kN
<b>Equipments</b>		
Air conditioning in electrical cabinet	●	●
VF driver software	●	●
DSTV file import	●	●
Telemaintenance	●	●
Marking unit with barrel	○	○
Disk marking unit - 40 characters	○	○
1600 kN notching on maxi 110 x 110 x 10 mm	○	○
Loading rotative arms	○	○
Unloading system on one side	●	●
Unloading system on both sides	○	○
Motorized (4,5 m) take-off table	●	●
Tilting section on 850 mm	○	○

○ Optional    ● Standard

VERNET BEHRINGER reserves the right to modify technical data without prior notice  
 Characteristics are given for E24 / ST37 steel